



WEBB

PRESENTS THE

CHAMP JR



MODEL 2VH

3HP HEAD



The Heaviest
of the
Heavyweights!

Weighing in at an impressive 2550 pounds, the Webb's "Champ" heavy duty, vari-speed powermill has an impressive list of standard features:

- Table size
- 9"x 42"
- 3 H.P. Main Drive Motor
- Class 7 Precision Bearings
- Precision Hardened and Ground Ways
- WayGuard Installed
- Superior Webb quality
- 12 Month No-Nonsense Guarantee

All Webb machine tools are unconditionally guaranteed and backed by the largest supply of warranty parts in the industry. And now with 130 Webb distributors nationally – a representative in every major city, we're bound to be near you. Call today for your local Webb distributor.

WEBB MODEL 2 - VH

HEAVY-DUTY, VARI-SPEED POWERMILL

Specifications*

Table
Standard Size 9" x 42" or 9" x 49"

Traverses

Longitudinal with 42" or 49" table size 30" OR 35"
Cross 12"
Vertical 18"
Ram 18"

Turret Head with 3 HP motor (Variable Speed)

Low-speed range, infinitely variable 60 to 500 R.P.M.
High- speed range, infinitely variable 500 to 4200 R.P.M.
Main spindle taper R-8
Spindle traverse 5"
Feeds per spindle revolution 0.0015"-0.003" – 0.0047"
Power of Motor 3 HP
Swivel of head +/- 90 degrees
Head tilt +/-45 degrees

Weight and Case Dimensions

New weight (approx.) 2550 lbs
Case dimensions (approx.) 64" x 54" x 68"

Same Factory since 1979
13,900 Sold in the USA
Highest Quality Machine Available

Standard Equipment & Features

- Turcite Coated Bed Ways
- Breaker Box 20 Amp
- Chromed Ways
- Way Covers
- Coolant sump in base
- One shot lubrication
- Roller bearing handles
- Class 7 precision spindle bearings
.00015" runout
- 220/440 30ph Electrics
- Instruction Book and Tool Box
- Meehanite casting
- 2 Part Epoxy Paint

Extra Equipment

- Power Feeds All Axis
- Servo longitudinal feed-box
- Air Automatic Draw Bars
- Vices
- Digital Readouts
- Coolant equipment
- R-8 collets, Clamp Kits
- Riser Blocks



Webb Machinery
Div. of Japan Machinery Corp.

17925 Collier Ave
Lake Elsinore, CA 92530

webbmachinery.com
(951) 277-8885

*Note: The manufacturer reserves the right to modify the design, specifications, mechanisms, etc, without notice