



WB - 1640G

WB - 1660G



Motor

Main spindle motor: 5 HP (3.7 kW)
Coolant pump motor: 1.8 HP

Dimensions & Weight

Machine net weight: 3,300 lbs
Machine Dimension (LxWxH) 82" x 34" 60" (1640)
102" x34"x60" (1660)

| Model | Spindle | Spindle Speed | Quick Change | Spindle Motor | FOB CA |
|----------|---------|---------------|--------------|---------------|----------|
| WB 1640G | D1-6 | 50-2000 rpm | OPT | 2.2kW (5HP) | \$14,750 |
| WB 1660G | D1-6 | 50-2000 rpm | OPT | 2.2kW (5HP) | \$16,450 |

Standard Accessories

| | | |
|-----------------------|------------------------------|--------------------------------|
| 5 HP main drive motor | D1-6 back plate 8" x 10" | MT4 center |
| MT6x4 center sleeve | 4-way tool post | Complete electric control unit |
| Change gears | 1/8HP coolant pump equipment | Rear splash guard |
| Rapid foot brake | Tool box and kits | Steady rest |
| Follow rest | 3-jaw scroll chick 8" | 4 jaw independent chuck 10" |
| Face plate 10" | | |

Optional Machine Accessories

| | |
|--|---------|
| Quick Change Tool post with 5 tool holders | \$690 |
| Taper turning Attachment | \$1390 |
| Face plate 14" | \$395 |
| 2-axis Accu-Rite DRO equipment for XY axis | \$1,990 |
| Installation of any 2-axis DRO | \$350 |
| Work Light (110V, 55W) | \$120 |
| Micro Stop | \$290 |
| JFK5C – Collet Closure | \$1,590 |
| Install Collet Closure | \$150 |

Additional Accessories Information

| | |
|--|-------------------------------------|
| Power requirement | 6.5 KVA 3 phase 208V to 203-V (max) |
| Air requirement | With opt. power draw bar 90-100 psi |
| Type of oil for way oil / pneumatic oil: | Mobil Vectra # 2 / Air Tool Oil |